



## Model: HK10S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

### # Engine

**Manufacturer** Kubota Diesel

**Engine Model** D1105

**Type & No. of Cylinder** Vertical, 4-cycle & 3 cylinders

**Induction** Spherical Type (E-TVCS)

**Engine Rated power** 8.4/11.4 KW/HP

**Fuel Consumption @ Load Percentage**

3.21L/hr@110%, 2.90L/hr@100%, 2.12L/hr@75%,  
1.48L/hr@50%

**Oil Capacity** 5.1 L

**Governor** Mechanical

### # Alternator

**Alternator Brand/Model** Stamford PI044E

**Exciter type** Brushless

**Prime Capacity** 10KVA

**Insulation** Class H

**Protection Class** IP23

### # Options

Water jacket heater, fuel heater, anti-condensation heater,  
permanent excitation, automatic fueling system, ATS,  
Extended run time fuel tank, sockets

### # Basic Data

**Prime Power** 10KVA/8KW

**Standby Power** 11KVA/9KW

**Model HK10S3, Silent type**

L: 1.63m W: 0.79m H: 1.08m 584kg

**Fuel Capacity:** 94L

**Noise Level:** 75 dBA/7m

### # Canopy (Silent Type)

**Skid** Bundled fuel tank with fork lift pockets

**Canopy** Lockable doors with control panel  
viewing window

**Finish** Galvanised and Powder Coated

**Emergency stop** External

### # Controls

**Controller** Deepsea 6020 with LCD Screen

**Circuit Breaker** Single pole

**Battery Charger** 12V DC