



Model: HK20S

/ 1 phase, 240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel

Engine Model V2203

Type & No. of Cylinder Vertical, 4-cycle & 4 cylinders

Induction Spherical Type (E-TVCS)

Engine Rated power 17.2/23.4 KW/HP

Fuel Consumption @ Load Percentage

5.55L/hr@110%, 4.90L/hr@100%, 3.58L/hr@75%,
2.50L/hr@50%

Oil Capacity 9.7 L

Governor Mechanical

Alternator

Alternator Brand/Model Stamford PI144G

Exciter type Brushless

Prime Capacity 18KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 18KVA/14.4KW

Standby Power 20KVA/16KW

Model HK20S, Silent type

L: 1.834m W: 0.868m H: 1.115m 684kg

Fuel Capacity: 100L

Noise Level: 75 dBA/7m

Canopy (Silent Type)

Skid Bunded fuel tank with fork lift pockets

Canopy Lockable doors with control panel
viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Single pole

Battery Charger 12V DC

Call US: 07 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Road, Biggera Waters,
Qld, 4216, Gold Coast, Australia

We reserve the right to modify the specifications without prior notice.