



Model: HK20S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel
Engine Model V2203
Type & No. of Cylinder Vertical, 4-cycle & 4 cylinders
Induction Spherical Type (E-TVCS)
Engine Rated power 17.2/23.4 KW/HP
Fuel Consumption @ Load Percentage
5.55L/hr@110%, 4.90L/hr@100%, 3.58L/hr@75%,
2.50L/hr@50%
Oil Capacity 9.7 L
Governor Mechanical

Alternator

Alternator Brand/Model Stamford PI144D
Exciter type Brushless
Prime Capacity 20KVA
Insulation Class H
Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 17KVA/13.6KW
Standby Power 19KVA/15.2KW
Model HK20S3, Silent type
L: 1.834m W: 0.868m H: 1.115m 644kg
Fuel Capacity: 100L
Noise Level: 72 dBA/7m

Canopy (Silent Type)

Skid Bundled fuel tank with fork lift pockets
Canopy Lockable doors with control panel
viewing window
Finish Galvanised and Powder Coated
Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen
Circuit Breaker Single pole
Battery Charger 12V DC

Call US: 0755006027

Power Master Generators Pty Ltd

Add: PO Box 550, Biggera Waters Qld, 4216, Australia
Ph 07 5500 6027

We reserve the right to modify the specifications without prior notice.