



Model: HC30E3/S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Cummins Diesel

Engine Model 4B3.9-G2

Type & Cylinder 4 stroke - 4L

Induction Naturally Aspirated

Engine Rated power 24/32 KW/HP

Fuel Consumption @ Load Percentage

8.3L/hr@110%, 7.5L/hr@100%, 6.9L/hr@75%,

4.5L/hr@50%

Coolant Capacity 19.6 L

Oil Capacity 10.9 L

Governor Electronic

Alternator

Alternator Brand/Model Stamford PI144G

Exciter type Brushless

Prime Capacity 30 KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fueling system, ATS, Extended run time fuel tank

Basic Data

Prime Power 30KVA/24KW

Standby Power 33KVA/26.4KW

Model HC40S3, Silent type

L:2.35m W:1.04m H: 1.63m 1168kg

Fuel Capacity 100L

Noise Level: 72dBA/7m

Model HC40E3, Open type

L:1.96m W:0.76m H: 1.45m 758kg

Fuel Capacity 115L

Noise Level: N/A

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets

Canopy Lockable doors with control panel viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Three pole

Battery Charger 24V DC

Call US: 0755290351

Gold Coast Generators Pty Ltd

Add: PO Box 470, Biggera Waters Qld, 4216, Australia
Ph 07 5529 0351

We reserve the right to modify the specifications without prior notice.