



Model: HC30E3/S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Cummins Diesel
Engine Model 4B3.9-G2
Type & Cylinder 4 stroke - 4L
Induction Naturally Aspirated
Engine Rated power 24/32 KW/HP
Fuel Consumption @ Load Percentage
8.3L/hr@110%, 7.5L/hr@100%, 6.9L/hr@75%,
4.5L/hr@50%
Coolant Capacity 19.6 L
Oil Capacity 10.9 L
Governor Electronic

Alternator

Alternator Brand/Model Stamford PI144G
Exciter type Brushless
Prime Capacity 30 KVA
Insulation Class H
Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank

Basic Data

Prime Power 30KVA/24KW
Standby Power 33KVA/26.4KW
Model HC40S3, Silent type
L:2.35m W:1.04m H: 1.63m 1168kg
Fuel Capacity 100L
Noise Level: 72dBA/7m
Model HC40E3, Open type
L:1.96m W:0.76m H: 1.45m 758kg
Fuel Capacity 115L
Noise Level: N/A

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets
Canopy Lockable doors with control panel
viewing window
Finish Galvanised and Powder Coated
Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen
Circuit Breaker Three pole
Battery Charger 24V DC

Call US: (07) 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Rd, Biggera Waters Qld,
4216, Australia Ph 07 5529 0351

We reserve the right to modify the specifications without prior notice.