



Model: HK6000S

/ 1 phase, 240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel

Engine Model Z482

Type & No.of Cylinder Vertical, 4-cycle&2 cylinders

Induction Spherical Type (E-TVCS)

Engine Rated power 8.3/11.3 KW/HP

Fuel Consumption @ Load Percentage

2.71L/hr@110%, 2.40L/hr@100%, 1.72L/hr@75%,

1.25L/hr@50%

Oil Capacity 2.5 L

Governor Mechanical

Alternator

Alternator Brand/Model Sincro EK2LAA

Exciter type Brushless

Prime Capacity 6KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fueling system, ATS, Extended run time fuel tank, sockets

Basic Data

Prime Power 5.5KVA/5.5KW

Standby Power 6KVA/6KW

Model HK6000S, Slient type

L:1.20m W:0.65m H: 0.8m 295kg

Fuel Capacity 28L

Noise Level: 75 dBA/7m

Canopy(Slient Type)

Skid Bunded fuel tank with fork lift pockets

Canopy Lockable doors with control panel viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Single pole

Battery Charger 12V DC