



## Model: HK6000S

/ 1 phase, 240V, 50HZ, 1500rpm /

### # Engine

Manufacturer Kubota Diesel  
Engine Model Z482  
Type & No. of Cylinder Vertical, 4-cycle & 2 cylinders  
Induction Spherical Type (E-TVCS)  
Engine Rated power 8.3/11.3 KW/HP  
Fuel Consumption @ Load Percentage  
2.71L/hr@110%, 2.40L/hr@100%, 1.72L/hr@75%,  
1.25L/hr@50%  
Oil Capacity 2.5 L  
Governor Mechanical

### # Alternator

Alternator Brand/Model Sincro EK2LAA  
Exciter type Brushless  
Prime Capacity 6KVA  
Insulation Class H  
Protection Class IP23

### # Options

Water jacket heater, fuel heater, anti-condensation heater,  
permanent excitation, automatic fueling system, ATS,  
Extended run time fuel tank, sockets

### # Basic Data

Prime Power 5.5KVA/5.5KW  
Standby Power 6KVA/6KW  
Model HK6000S, Slient type  
L:1.20m W:0.65m H: 0.8m 295kg  
Fuel Capacity 28L  
Noise Level: 75 dBA/7m

### # Canopy (Slient Type)

Skid Bunded fuel tank with fork lift pockets  
Canopy Lockable doors with control panel  
viewing window  
Finish Galvanised and Powder Coated  
Emergency stop External

### # Controls

Controller Deepsea DSE4520 with LCD  
Screen Circuit Breaker Single pole  
Battery Charger 12V DC

Call US: 07 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Road, Biggera Waters,  
Qld, 4216, Gold Coast, Australia

We reserve the right to modify the specifications without prior notice.