



## Model: HC60S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

### # Engine

**Manufacturer** Cummins Diesel  
**Engine Model** 4BTA3.9-G2  
**Type & Cylinder** 4 stroke - 4 cylinders  
**Induction** Turbocharged  
**Engine Rated power** 50/67 KW/HP  
**Fuel Consumption @ Load Percentage**  
16L/hr@110%, 14.5L/hr@100%, 10L/hr@75%,  
6.9L/hr@50%  
**Coolant Capacity** 20.8 L  
**Oil Capacity** 10.9 L  
**Governor** Electronic

### # Alternator

**Alternator Brand/Model** Stamford UCI224E  
**Exciter type** Brushless  
**Prime Capacity** 60 KVA  
**Insulation** Class H  
**Protection Class** IP23

### # Options

Water jacket heater, fuel heater, anti-condensation heater,  
permanent excitation, automatic fueling system, ATS,  
Extended run time fuel tank

### # Basic Data

**Prime Power** 60KVA/48KW  
**Standby Power** 66KVA/53KW  
**Model HC60S3, Silent type**  
L:2.596m W:1.1m H: 1.657m 1620kg  
12 hours Fuel Capacity 155L  
Noise Level: 73dBA/7m

### # Canopy(Silent Type)

**Skid** Bunded fuel tank with fork lift pockets  
**Canopy** Lockable doors with control panel  
viewing window  
**Finish** Galvanised and Powder Coated  
**Emergency stop** External

### # Controls

**Controller** Deepsea 6020 with LCD Screen  
**Circuit Breaker** Three pole  
**Battery Charger** 24V DC

Call US: 0755290351

Gold Coast Generators Pty Ltd

Add: PO Box 470, Biggiera Waters Qld, 4216, Australia  
Ph 07 5529 0351

We reserve the right to modify the specifications without prior notice.