



Model: HK10S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel

Engine Model D1105

Type & No. of Cylinder Vertical, 4-cycle & 3 cylinders

Induction Spherical Type (E-TVCS)

Engine Rated power 8.4/11.4 KW/HP

Fuel Consumption @ Load Percentage

3.21L/hr@110%, 2.90L/hr@100%, 2.12L/hr@75%,
1.48L/hr@50%

Oil Capacity 5.1 L

Governor Mechanical

Alternator

Alternator Brand/Model Stamford PI044E

Exciter type Brushless

Prime Capacity 10KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 10KVA/8KW

Standby Power 11KVA/9KW

Model HK10S3, Silent type

L: 1.63m W: 0.79m H: 1.08m 584kg

Fuel Capacity: 94L

Noise Level: 75 dBA/7m

Canopy (Silent Type)

Skid Bundled fuel tank with fork lift pockets

Canopy Lockable doors with control panel
viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Single pole

Battery Charger 12V DC