



07 5500 6027

info@powermastergenerators.com.au

Model: HK8000S

/ 1 phase, 240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel

Engine Model D722

Type & No. of Cylinder Vertical, 4-cycle & 3 cylinders

Induction Spherical Type (E-TVCS)

Engine Rated power 12.4/16.9 KW/HP

Fuel Consumption @ Load Percentage

3.72L/hr@110%, 3.30L/hr@100%, 2.41L/hr@75%,
1.69L/hr@50%

Oil Capacity 3.8 L

Governor Mechanical

Alternator

Alternator Brand/Model Sincro EK2LCA

Exciter type Brushless

Prime Capacity 8KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 8KVA/8KW

Standby Power 8.8KVA/8.8KW

Model HK8000S, Silent type

L: 1.285m W: 0.65m H: 0.8m 320kg

Fuel Capacity 28L

Noise Level: 75 dBA/7m

Canopy (Silent Type)

Skid Bundled fuel tank with fork lift pockets

Canopy Lockable doors with control panel
viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea DSE4520 with LCD

Screen Circuit Breaker Single pole

Battery Charger 12V DC