

Engine

Manufacturer Cummins Diesel
Engine Model NTA855-G2A
Type & Cylinder 4 stroke - 6L
Induction Turbocharged
Engine Rated power 310/415 KW/HP
Fuel Consumption @ Load Percentage
83L/hr@110%, 73L/hr@100%, 57L/hr@75%,
40L/hr@50%
Coolant Capacity 60.6L
Oil Capacity 38.6 L
Governor Electronic

Alternator

Alternator Brand/Model Stamford HCI444E Exciter type Brushless Prime Capacity 350KVA Insulation Class H Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fueling system, ATS, Extended run time fuel tank

Basic Data

Prime Power 350KVA/280KW Standby Power 385KVA/308KW Model HC350S3, Slient type L:3.83m W:1.4m H: 2.161m 4298kg Fuel Capacity 560L Noise Level: 75dBA/7m

Canopy(Slient Type)

Skid Bunded fuel tank with fork lift pockets Canopy Lockable doors with control panel viewing window Finish Galvanised and Powder Coated Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen Circuit Breaker Three pole Battery Charger 24V DC