



Model: HC60E3/S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Cummins Diesel
Engine Model 4BTA3.9-G2
Type & Cylinder 4 stroke - 4L
Induction Turbocharged
Engine Rated power 50/67 KW/HP
Fuel Consumption @ Load Percentage
16L/hr@110%, 14.5L/hr@100%, 10L/hr@75%,
6.9L/hr@50%
Coolant Capacity 20.8 L
Oil Capacity 10.9 L
Governor Electronic

Alternator

Alternator Brand/Model Stamford UCI224E
Exciter type Brushless
Prime Capacity 60 KVA
Insulation Class H
Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank

Basic Data

Prime Power 60KVA/48KW
Standby Power 66KVA/53KW
Model HC60S3, Silent type
L:2.6m W:1.1m H: 1.65m 1580kg
Fuel Capacity 205L (may vary)
Noise Level: 73dBA/7m
Model HC60E3, Open type
L:1.96m W:0.76m H: 1.45m 930kg
Fuel Capacity 130L
Noise Level: N/A

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets
Canopy Lockable doors with control panel
viewing window
Finish Galvanised and Powder Coated
Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen
Circuit Breaker Three pole
Battery Charger 24V DC

Call US: 07 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Road, Biggera Waters,
Qld, 4216, Gold Coast, Australia

We reserve the right to modify the specifications without prior notice.