

GENERAL

Model: HP20S

Prime Power: 20KVA/16KW Standby Power: 22KVA/17.6KW

Rated Voltage: 240V. Frequency: 50HZ Speed: 1500RPM Noise Level: 72dB@7m 70L

Fuel Tank Capacity:

ENGINE

Model: 404D-22G **Brand: Perkins**

4 Stroke, 4 Cylinder Diesel **Engine Type:**

Induction: Naturally aspirated

Displacement: 2.216L

Continuous Output: 20.3KW@1500rpm

Coolant Capacity: 7.0L Oil Capacity: 10.6L

Speed Governor: Mechanical

6.1L/H@110%, 5.3L/H@100% **Fuel Consumption:**

4.0L/H@75%, 2.9L/H@50%

ALTERNATOR

Model: PI144G **Brand:** Stamford KW Base Rate(BR): 16.3KW **Exciting Type: Brushless Insulation Class:** Class H **Protection Class:**

Unit

Generator Type: Silent Type

Dimensions(LxWxH): 1930x850x1256mm

Dry Weight: 850kas

Controls

Model: **DSE6020 Brand:** Deepsea

Display: LCD and LED alarm indication

Sockets: 3x15A.1P **Battery Charger: 12V DC**

Options

Water jacket heater, oil preheater,

anti-condensation heater, fuel water separator,

fuel heater, automatic fueling system.

Canopy

Bunded fuel tank with forklift pockets, center

lift lug, weather resistant, lockable doors with Skid:

control panel viewing window. Canopy:

Galvanized, Powder coated finish, sound Finish:

reducing canopy external with stainless steel

Application

- * Mining sites * Emergency solutions
- * Construction sites * Outdoor events
- * Military bases * Agricultural applications