



Model: HC114E3/S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Cummins Diesel

Engine Model 6BTA5.9-G2

Type & Cylinder 4 stroke - 6L

Induction Turbocharged

Engine Rated power 106/142 KW/HP

Fuel Consumption @ Load Percentage

30L/hr@110%, 27L/hr@100%, 20L/hr@75%,

14L/hr@50%

Coolant Capacity 28 L

Oil Capacity 14.2 L

Governor Electronic

Alternator

Alternator Brand/Model Stamford UCI274D

Exciter type Brushless

Prime Capacity 120 KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fueling system, ATS, Extended run time fuel tank

Basic Data

Prime Power 114KVA/91KW

Standby Power 125KVA/100KW

Model HC114S3, Silent type

L:3m W:1.1m H: 1.749m 2045kg

Fuel Capacity 200L

Noise Level: 75dBA/7m

Model HC114E3, Open type

L:2.4m W:0.95m H: 1.6m 1230kg

Fuel Capacity 240L

Noise Level: N/A

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets

Canopy Lockable doors with control panel viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Three pole

Battery Charger 24V DC

Call US: 07 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Road, Biggera Waters, Qld, 4216, Gold Coast, Australia

We reserve the right to modify the specifications without prior notice.