



Model: HC131E3/S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Cummins Diesel

Engine Model 6BTAA5.9-G2

Type & Cylinder 4 stroke - 6L

Induction Turbocharged

Engine Rated power 120/161 KW/HP

Fuel Consumption @ Load Percentage

35L/hr@110%, 31L/hr@100%, 23L/hr@75%,

16L/hr@50%

Coolant Capacity 34 L

Oil Capacity 14.2 L

Governor Electronic

Alternator

Alternator Brand/Model Stamford UCI274E

Exciter type Brushless

Prime Capacity 140 KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fueling system, ATS, Extended run time fuel tank

Basic Data

Prime Power 131KVA/105KW

Standby Power 144KVA/115KW

Model HC131S3, Silent type

L:3m W:1.1m H: 1.749m 2076kg

Fuel Capacity 200L

Noise Level: 75dBA/7m

Model HC131E3, Open type

L:2.4m W:0.95m H: 1.6m 1310kg

Fuel Capacity 240L

Noise Level: N/A

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets

Canopy Lockable doors with control panel viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Three pole

Battery Charger 24V DC

Call US: 07 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Road, Biggerra Waters, Qld, 4216, Gold Coast, Australia

We reserve the right to modify the specifications without prior notice.