



Model: HC250S3

GENERAL

Model:	HC250S3
Prime Power:	250KVA/200KW
Standby Power:	275KVA/220KW
Rated Voltage:	415/240V,3P
Frequency:	50HZ
Speed:	1500RPM
Noise Level:	75dBA@7m
Fuel Tank Capacity:	430L

ENGINE

Model:	6LTAA8.9-G2
Brand:	Cummins
Engine Type:	4 Stroke, 6 Cylinder Diesel
Induction:	Turbocharged
Displacement:	8.9L
Continuous Output:	220KW
Coolant Capacity:	50.3L
Oil Capacity:	27.6L
Speed Governor:	Electronic
Fuel Consumption:	60L/H@110%, 53L/H@100% 41L/H@75%, 38L/H@50%

ALTERNATOR

Model:	UCDI274K
Brand:	Stamford
KW Base Rate(BR):	200KW
Exciting Type:	Brushless
Insulation Class:	Class H
Protection Class:	IP23

Unit

Generator Type:	Silent Type
Dimensions(L*W*H):	3600x1300x2000mm
Dry Weight:	3050kgs

Controller

Model:	DSE6020
Brand:	Deepsea
Display:	LCD and LED alarm indication
Function:	Monitoring engine speed, oil pressure, coolant temperature, frequency, voltage, current, power and fuel level

CONFIGURATION

Standard: engine, alternator, cooling system, base frame, control box.

Optional: Water jacket heater, oil preheater, anti-condensation heater, fuel water separator, fuel heater, fuel level sensor, water level sensor, automatic fueling system.

APPLICATION

>> Mining sites	>> Emergency solution
>> Construction sites	>> Outdoor events
>> Military bases	>> Special events

Call US: 0755006027

POWER MASTER GENERATORS PTY LTD

Add: Unit 30/211 Brisbane Road, Biggera Waters Qld, 4216, Australia

We reserve the right to modify the specifications without prior notice.