



Model: HK20S

/ 1 phase, 240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel
Engine Model V2203
Type & No. of Cylinder Vertical, 4-cycle & 4 cylinders
Induction Spherical Type (E-TVCS)
Engine Rated power 17.2/23.4 KW/HP
Fuel Consumption @ Load Percentage
5.55L/hr@110%, 4.90L/hr@100%, 3.58L/hr@75%,
2.50L/hr@50%
Oil Capacity 9.7 L
Governor Mechanical

Alternator

Alternator Brand/Model Stamford PI144G
Exciter type Brushless
Prime Capacity 18KVA
Insulation Class H
Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank, sockets

Basic Data

Prime Power 18KVA/14.4KW
Standby Power 20KVA/16KW
Model HK20S, Silent type
L: 1.834m W: 0.868m H: 1.115m 684kg
Fuel Capacity: 100L
Noise Level: 75 dBA/7m

Canopy (Silent Type)

Skid Bunded fuel tank with fork lift pockets
Canopy Lockable doors with control panel
viewing window
Finish Galvanised and Powder Coated
Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen
Circuit Breaker Single pole
Battery Charger 12V DC

Call US: 07 5500 6027

Power Master Generators

Add: Unit 30/211 Brisbane Road, Biggerra Waters,
Qld, 4216, Gold Coast, Australia

We reserve the right to modify the specifications without prior notice.