



Model: HK25S3

/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Kubota Diesel

Engine Model V3300

Type & No. of Cylinder Vertical, 4-cycle & 4 cylinders

Induction Natural aspirated

Engine Rated power 26.3/35.8 KW/HP

Fuel Consumption @ Load Percentage

7.7L/hr@100%, 5.9L/hr@75%, 4.3L/hr@50%,

3.2L/hr@25%

Oil Capacity 13.2L

Governor Mechanical

Alternator

Alternator Brand/Model Stamford PI144E

Exciter type Brushless

Prime Capacity 25KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fueling system, ATS, Extended run time fuel tank, sockets

Basic Data

Prime Power 25KVA/20KW

Standby Power 27.5KVA/22KW

Model HK25S3, Silent type

L: 2.1m W: 0.966m H: 1.115m 901kg

Fuel Capacity: 114L

Noise Level: 72 dBA/7m

Canopy (Silent Type)

Skid Bundled fuel tank with fork lift pockets

Canopy Lockable doors with control panel viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Single pole

Battery Charger 12V DC