



Model: HC60S3

HC
/ 3 phase, 415/240V, 50HZ, 1500rpm /

Engine

Manufacturer Cummins Diesel

Engine Model 4BTA3.9-G2

Type & Cylinder 4 stroke - 4 cylinders

Induction Turbocharged

Engine Rated power 50/67 KW/HP

Fuel Consumption @ Load Percentage

16L/hr@110%, 14.5L/hr@100%, 10L/hr@75%,
6.9L/hr@50%

Coolant Capacity 20.8 L

Oil Capacity 10.9 L

Governor Electronic

Alternator

Alternator Brand/Model Stamford UCI224E

Exciter type Brushless

Prime Capacity 60 KVA

Insulation Class H

Protection Class IP23

Options

Water jacket heater, fuel heater, anti-condensation heater,
permanent excitation, automatic fueling system, ATS,
Extended run time fuel tank

Basic Data

Prime Power 60KVA/48KW

Standby Power 66KVA/53KW

Model HC60S3, Silent type

L:2.596m W:1.1m H: 1.657m 1620kg

12 hours Fuel Capacity 155L

Noise Level: 73dBA/7m

Canopy(Silent Type)

Skid Bunded fuel tank with fork lift pockets

Canopy Lockable doors with control panel
viewing window

Finish Galvanised and Powder Coated

Emergency stop External

Controls

Controller Deepsea 6020 with LCD Screen

Circuit Breaker Three pole

Battery Charger 24V DC

Call US: 07 5500 6027

Power Master Generators Pty Ltd

Add: Unit 30/211 Brisbane Road, Biggera Waters,
Qld, 4216

We reserve the right to modify the specifications without prior notice.