

GENERATOR SPECIFICATIONS









Power Master – EPS15IA-1

GENERATOR SALES & HIRE PORTABLE POWER STATIONS BATTERIES - PRESSURE WASHERS COMPRESSORS - WATER PUMPS

[07] 5500 6027

































Generator Specification Sheet Power Master Diesel Generator – EPS15IA-1 Single Phase



DESCRIPTION

The <u>EPS15IA-1</u> Silent Diesel Generator is a reliable and robust power solution, designed to meet diverse requirements across various industries. Offering optimal performance, durability, and efficiency, this generator is built with high-quality components, including an Isuzu engine, ensuring reliable power output for both prime and standby applications. The weather-resistant, sound-reducing canopy makes it ideal for outdoor and demanding Australian environments to protect and prolong the life of your generator, finished using a powder coated paint finish. Below are the key specifications, applications, and optional features of the <u>EPSI5IA-1</u> model.

This versatile and reliable generator is designed to provide consistent power while being easy to maintain and transport. For any questions or to confirm up-to-date specifications, please contact us directly or check our website for updates.

APPLICATION

- Mining sites
- Emergency solutions
- Construction sites
- Outdoor events
- Military bases
- Agricultural applications

OPTIONS

Stainless steel canopy, water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fuelling system, ATS, extended run time fuel tank.

CANOPY

Canopy: Weather resistant silenced canopy designed for harsh Australian outdoor, bunded fuel tank with forklift pockets.

Panel: Lockable doors, stainless steel fittings with control panel viewing window.

Finish: Galvanized, Powder coated finish, sound reducing canopy external with stainless steel fittings & hinges.



































Generator Specification Sheet Power Master Diesel Generator – EPS15IA-1 Single Phase

SPECIFICATIONS

Model: EPSI5IA-1
Prime Power: 15KVA/15KW
Standby Power: 16.5KVA/16.5KW
Rated Voltage: 240V,
Frequency: 50HZ
Speed: 1500RPM
Noise Level: 68dB@7m

Phase Three Phase + Single phase

621

ENGINE

Fuel Tank Capacity:

Model: JE493DB-04

Brand: Isuzu

Engine Type: 4 Stroke, 4 Cylinder Diesel Induction: Naturally aspirated

Coolant Capacity: 7.8L

Oil Capacity: 5.6L

Governor: Mechanical

Optional Upgrades

Fire extinguisher
Battery & starter Isolator
Solar battery charger
3 -way fuel valve
Cell phone monitoring

UNIT

Generator Type: Silent Type

Dimensions (LxWxH): 190 x 90 x 113cm

Dry Weight: 800kgs

CONTROLS

Model: DSE4520
Brand: Deepsea

Display: LCD and LED alarm indication

Outlets (IP66): 3x15A, (1P) & 1x 32A, (1P)

Battery Charger: 12V DC Circuit Breaker: 2 Pole

ALTERNATOR

Model: EPA184ES
Brand: Acelite

KW Base Rate(BR): 15KW/18.8kVA

Exciting Type: Brushless
Insulation Class: Class H
Protection Class: IP23

Every effort has been made to ensure the accuracy of the details outlined in this document. However, the specifications are provided by our suppliers and may be subject to change without prior notice. We regularly update our website with any changes as soon as they are advised. Please contact us to confirm that the information provided is current.































