



GENERATOR SPECIFICATIONS



Power Master – EPS30IA-3

GENERATOR SALES & HIRE
PORTABLE POWER STATIONS
BATTERIES – PRESSURE WASHERS
COMPRESSORS – WATER PUMPS
(07) 5500 6027



WWW.POWERMASTERGENERATORS.COM.AU



DESCRIPTION

The EPS30IA-3 Silent Diesel Generator is a reliable and robust power solution, designed to meet diverse requirements across various industries. Offering optimal performance, durability, and efficiency, this generator is built with high-quality components, including an Isuzu engine, ensuring reliable power output for both prime and standby applications. The weather-resistant, sound-reducing canopy makes it ideal for outdoor and demanding Australian environments to protect and prolong the life of your generator, finished using a powder coated paint finish. Below are the key specifications, applications, and optional features of the EPS30IA-3 model.

This versatile and reliable generator is designed to provide consistent power while being easy to maintain and transport. For any questions or to confirm up-to-date specifications, please contact us directly or check our website for updates.

APPLICATION

- Mining sites
- Emergency solutions
- Construction sites
- Outdoor events
- Military bases
- Agricultural applications

OPTIONS

Stainless steel canopy, water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fuelling system, ATS, extended run time fuel tank.

CANOPY

Canopy: Weather resistant silenced canopy designed for harsh Australian outdoor, bunded fuel tank with forklift pockets.

Panel: Lockable doors, stainless steel fittings with control panel viewing window.

Finish: Powder coated finish, sound reducing canopy external with stainless steel fittings & hinges.

SPECIFICATIONS

GENERAL		UNIT	
Model:	EPS30IA-3	Generator Type:	Silent Type
Prime Power:	30KVA/25KW	Dimensions (LxWxH):	205 x 90 x 113cm
Standby Power:	33KVA/27.5KW	Dry Weight:	870kgs
Engine Rated Power:	28KW/38HP	CONTROLS	
Rated Voltage:	415V		
Frequency:	50HZ		
Speed:	1500RPM		
Noise Level:	68dB@7m		
Fuel Tank Capacity:	100L	Model:	DSE4520
Phase	Three Phase (Single Phase available)	Brand:	Deepsea
Battery Isolator:	Standard	Display:	LCD and LED alarm indication
ENGINE		Outlets (IP66):	3x15A, (1P) & 1 x 32A, (3P)
		Battery Charger:	12V DC
		Circuit Breaker:	4 Pole
		ALTERNATOR	
		Model:	EPA184G
Brand:	Isuzu	Brand:	Acelite
Engine Type:	4 Stroke, 4 Cylinder Diesel	KW Base Rate(BR):	25KW/32kVA
Induction:	Turbo charged	Exciting Type:	Brushless
Coolant Capacity:	8.8L	Insulation Class:	Class H
Oil Capacity:	5.6L	Protection Class:	IP23
Governor	Mechanical		
Battery Isolator:	Standard		
Warranty: 2 years/1000 hrs (whichever comes first)			
Optional Upgrades			
Fire extinguisher			
Battery & starter Isolator			
Solar battery charger			
3 -way fuel valve			
Cell phone monitoring			

Every effort has been made to ensure the accuracy of the details outlined in this document. However, the specifications are provided by our suppliers and may be subject to change without prior notice. We regularly update our website with any changes as soon as they are advised. Please contact us to confirm that the information provided is current.