

GENERATOR SPECIFICATIONS









Power Master – EPS10IA-1

GENERATOR SALES & HIRE PORTABLE POWER STATIONS BATTERIES - PRESSURE WASHERS COMPRESSORS - WATER PUMPS

[07] 5500 6027

































Generator Specification Sheet Power Master Diesel Generator – EPS10A-1 Single Phase



DESCRIPTION

The <u>EPSIOIA-1</u> Silent Diesel Generator is a reliable and robust power solution, designed to meet diverse requirements across various industries. Offering optimal performance, durability, and efficiency, this generator is built with high-quality components, including an Isuzu engine and Acelite alternator, ensuring reliable power output for both prime and standby applications. The weather-resistant, sound-reducing canopy makes it ideal for outdoor and demanding Australian environments to protect and prolong the life of your generator, finished using a powder coated paint finish. Below are the key specifications, applications, and optional features of the <u>EPSIOIA-1</u> model.

This versatile and reliable generator is designed to provide consistent power while being easy to maintain and transport. For any questions or to confirm up-to-date specifications, please contact us directly or check our website for updates.

APPLICATION

- Mining sites
- Emergency solutions
- Construction sites
- Outdoor events
- Military bases
- Agricultural applications

OPTIONS

Stainless steel canopy, water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fuelling system, ATS, extended run time fuel tank.

CANOPY

Canopy: Weather resistant silenced canopy designed for harsh Australian outdoor, bunded fuel tank with forklift pockets.

Panel: Lockable doors, stainless steel fittings with control panel viewing window.

Finish: Powder coated finish, sound reducing canopy external with stainless steel fittings & hinges.



































Generator Specification Sheet Power Master Diesel Generator – EPS10A-1 Single Phase

SPECIFICATIONS

GENERAL UNIT Model: EPSIOIA-1 Generator Type: Silent Type 190 x 90 x 113cm Prime Power: 10KVA/10KW Dimensions (LxWxH): Standby Power: Dry Weight: 11KVA/11KW 780kgs Rated Voltage: 240V,

Frequency: 50HZ CONTROLS

Speed: 1500RPM Model: DSE4520

Noise Level: 63dB@7m Brand: Deepsea

Fuel Tank Capacity: 62L Display: LCD and LED alarm indication
Phase Single Phase

Sockets: 3x15A(1P) (optional selection)

ENGINE Battery Charger: 12V DC

Model: JE493DB-04 Circuit Breaker: 2 Pole

Brand: Isuzu ALTERNATOR

Engine Type: 4 Stroke, 4 Cylinder Diesel Model: EPA164C Induction: Naturally aspirated Brand: Acelite

Coolant Capacity: 7.8L KW Base Rate(BR): 10.8KW/13.5kVA

Oil Capacity: 5.6L Exciting Type: Brushless
Governor: Mechanical Insulation Class: Class H

Engine Rated Power: 21KW/28HP Protection Class: IP23

Warranty: 2 years/1000

(whichever comes first /battery

Optional Upgrades

Fire extinguisher
Battery & starter Isolator
Solar battery charger
3 -way fuel valve
Cell phone monitoring

Every effort has been made to ensure the accuracy of the details outlined in this document. However, the specifications are provided by our suppliers and may be subject to change without prior notice. We regularly update our website with any changes as soon as they are advised. Please contact us to confirm that the information provided is current.































