

POWER MASTER

GENERATORS & POWER EQUIPMENT

GENERATOR SPECIFICATIONS



Power Master – EPS20KS-1

GENERATOR SALES & HIRE
PORTABLE POWER STATIONS
BATTERIES - PRESSURE WASHERS
COMPRESSORS - WATER PUMPS

(07) 5500 6027



WWW.POWERMASTERGENERATORS.COM.AU



DESCRIPTION

The EPS20KS-1 Silent Diesel Generator is a reliable and robust power solution, designed to meet diverse requirements across various industries. Offering optimal performance, durability, and efficiency, this generator is built with high-quality components, including a Kubota engine, ensuring reliable power output for both prime and standby applications. The weather-resistant, sound-reducing canopy makes it ideal for outdoor and demanding Australian environments to protect and prolong the life of your generator, finished using a powder coated paint finish. Below are the key specifications, applications, and optional features of the EPS20KS-1 model.

This versatile and reliable generator is designed to provide consistent power while being easy to maintain and transport. For any questions or to confirm up-to-date specifications, please contact us directly or check our website for updates.

APPLICATION

- Mining sites
- Emergency solutions
- Construction sites
- Outdoor events
- Military bases
- Agricultural applications

OPTIONS

Stainless steel canopy, water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fuelling system, ATS, extended run time fuel tank.

CANOPY

Canopy: Weather resistant silenced canopy designed for harsh Australian outdoor, bunded fuel tank with forklift pockets.

Panel: Lockable doors, stainless steel fittings with control panel viewing window.

Finish: Powder coated finish, sound reducing canopy external with stainless steel fittings & hinges.



SPECIFICATIONS

GENERAL		UNIT	
Model:	EPS20KS-1	Generator Type:	Silent Type
Prime Power:	20KVA/16KW	Dimensions (LxWxH):	2050 x 900 x 1250cm
Standby Power:	22KVA/17.6KW	Dry Weight:	850kgs
Rated Voltage:	415/240V		
Frequency:	50HZ	CONTROLS	
Speed:	1500RPM	Model:	DSE4520
Noise Level:	63dB@7m	Brand:	Deepeer
Fuel Tank Capacity:	100L	Display:	LCD and LED alarm indication
Phase	Single Phase (Three phase available)	Sockets:	3x15A, (1P) & 1x32A, (3P)
ENGINE		Battery Charger:	12V DC
Model:	V2003T	Circuit Breaker:	4 Pole
Brand:	Kubota	ALTERNATOR	
Engine Type:	Vertical, 4 Cylinder Diesel Spherical Type (E-TVCS)	Model:	PI144E
Coolant Capacity:	8.1L	Brand:	Stamford
Oil Capacity:	7.6L	KW Base Rate(BR):	18.4KW/20kVA
Governor	Mechanical	Exciting Type:	Brushless
Engie Rated Power:	22.5KW	Insulation Class:	Class H
		Protection Class:	IP23

Optional Upgrades

- Fire extinguisher
- Battery & starter Isolator
- Solar battery charger
- 3 -way fuel valve
- Cell phone monitoring
- Rental/Mine spec

Every effort has been made to ensure the accuracy of the details outlined in this document. However, the specifications are provided by our suppliers and may be subject to change without prior notice. We regularly update our website with any changes as soon as they are advised. Please contact us to confirm that the information provided is current.