



# GENERATOR SPECIFICATIONS



Power Master – EPS60CL-3

**GENERATOR SALES & HIRE**  
**PORTABLE POWER STATIONS**  
**BATTERIES - PRESSURE WASHERS**  
**COMPRESSORS - WATER PUMPS**  
**(07) 5500 6027**



**MAXWATT**

**DUNLITE**

**Kubota**

**HYUNDAI**  
POWER PRODUCTS

**W&C** WELLING & CROSSLEY

**Westinghouse**

**GENERAC**

**HONDA**  
POWER PRODUCTS

**CATERPILLAR**

**ISUZU**

**YANMAR**

**PRAMAC**

**CROMMELINS**

**Onan**

**ACDelco**

**WWW.POWERMASTERGENERATORS.COM.AU**



## DESCRIPTION

The **EPS60CL-3** Silent Diesel Generator is a reliable and robust power solution, designed to meet diverse requirements across various industries. Offering optimal performance, durability, and efficiency, this generator is built with high-quality components, including a **Cummins** engine, ensuring reliable power output for both prime and standby applications. The weather-resistant, sound-reducing canopy makes it ideal for outdoor and demanding Australian environments to protect and prolong the life of your generator, galvanized and finished using a galvanized powder coated paint finish. Below are the key specifications, applications, and optional features of the **EPS60CL-3** model.

This versatile and reliable generator is designed to provide consistent power while being easy to maintain and transport. For any questions or to confirm up-to-date specifications, please contact us directly or check our website for updates.

## APPLICATION

- Mining sites
- Emergency solutions
- Construction sites
- Outdoor events
- Military bases
- Agricultural applications

## OPTIONS

Stainless steel canopy, water jacket heater, fuel heater, anti-condensation heater, permanent excitation, automatic fuelling system, ATS, extended run time fuel tank.

## CANOPY

**Canopy:** Weather resistant silenced canopy designed for harsh Australian outdoor, bunded fuel tank with forklift pockets.

**Panel:** Lockable doors, stainless steel fittings with control panel viewing window.

**Finish:** Powder coated finish, sound reducing canopy external with stainless steel fittings & hinges.

## SPECIFICATIONS

GENERAL		UNIT	
Model:	EPS60CL-3	Generator Type:	Silent Type
Prime Power:	60KVA	Dimensions (LxWxH):	240x100x178cm
Standby Power:	66KVA	Dry Weight:	1450kgs
Rated Voltage:	415V,	<b>CONTROLS</b>	
Frequency:	50HZ		
Speed:	1500RPM	Model:	DSE6020
Noise Level:	69dB@7m	Brand:	Deepsea
Fuel Tank Capacity:	350L	Display:	LCD and LED alarm indication
Phase	Three Phase		
Battery Isolator:	Standard		
ENGINE		Outlets (IP66):	2 x 32A (3P), 3 x 15A (1P)
Model:	4BTA3.9-G2	Battery Charger:	24V DC
Brand:	Cummins	Circuit Breaker:	4 Pole
Engine Type:	4 Stroke Cylinder Diesel	ALTERNATOR	
Induction:	Turbo charged	Model:	TAL-A42H
Coolant Capacity:	20.8L	Brand:	Leroy Somer
Oil Capacity:	10.9L	KW Base Rate (BR):	63KVA
Governor	Electronic	Exciting Type:	Brushless
<b>*Optional Upgrades*</b> Fire extinguisher Battery & starter Isolator Solar battery charger 3 -way fuel valve Cell phone monitoring Rental/Mine Spec Automatic Transfer Switch (ATS) Special Builds Welcome!		Insulation Class:	Class H
		Protection Class:	IP23

*Every effort has been made to ensure the accuracy of the details outlined in this document. However, the specifications are provided by our suppliers and may be subject to change without prior notice. We regularly update our website with any changes as soon as they are advised. Please contact us to confirm that the information provided is current.*