



FIRE FIGHTING - IRRIGATION - WATER TRANSFER - TRASH

4" TRASH PUMP

MH40TE-2

The MH40TE-2, 4" trash pump is powered by a Honda GX270 petrol electric start engine. This pump is designed to safely move contaminated water without being damaged. It is ideal for a range of tasks such as moving water containing solids (e.g. flood water), effluent pumping, slurry pumping and water transfer.


The pump is made from heavy duty cast iron and features a big, closed impeller that is resistant to wear. The quick release system allows rapid access to the impeller for removing debris. The MH40TE-2 is capable of safely moving solids up to 28mm in diameter. A sturdy rollover frame makes for easy portability and protection of this hardworking pump.

The hard wearing reliability, impressive performance and portability make this pump a popular choice for industrial and agricultural applications. SES brigades rely on this model for those reasons.



POWERED by
HONDA™

MH40TE-2 PUMP PERFORMANCE CURVE



TECHNICAL SPECIFICATIONS:

Engine	: Honda GX270
Starting System	: Electric
Fuel Tank Capacity	: 5.3 L
Suction Size	: 4"
Discharge Size	: 4"
Max. Head	: 28m
Max. Flow Rate	: 2000 L/min
Fuel Type	: Unleaded Petrol
Dimensions (L x W x H)	: 740 x 540 x 600 mm
Dry Weight	: 85 kg

Specifications subject to change without notice.

SPECIALISTS IN DESIGNING TOUGH PUMPS FOR AUSTRALIAN CONDITIONS

(07) 5500 6027 powermastergenerators.com.au

* Specifications are subject to change without notice. Images are for display purposes only. Product may differ from images displayed. Performance data has been measured at the pump. The performance of our Pumps as noted above can be affected by the installation and configuration of the pipe work and distances involved. Example - suction head, static head, friction head. Which all need to be considered when determining the appropriate pump size.

