

Westinghouse

The new iGen4750PRO combines high-output performance with enhanced electrical safety protection to meet the needs of professional users. It features electric start, remote control, and an integrated RCD safety switch, all within a compact and portable unit. Designed for reliability, ease of use and workplace compliance, the iGen4750PRO is an ideal power source for tools, equipment, and demanding jobsite use.

iGen4750PRO Inverter Generator

3800 | **4750**
Running Watts | Starting Watts



Features and Benefits

Powerful

Highest starting and running power outputs in its class.

Remote Control

Convenient push-button start and stop from a distance.

LED Lights

Illuminate control panel for night-time operation.

Lightweight

Portable at just 36 kg with handles and wheels.

Long Running

Up to 14 hours at 1/4 load with a 12 litre fuel tank.

Plug and Play

No assembly required, just add petrol.

Electric Start

One touch power-up from the onboard 12-Volt battery.

Electrical Safety Protection

RCD safety switch approved for workplace use.

Battery Charger

Keep your generator ready to go at all times.

Super Quiet

Low noise level ideal for workplace use.

Mains Quality Electricity

Safe to power sensitive electronic equipment.

Warranty Protection

2-year domestic use (conditions apply).



Control Panel Functions

Engine Control Button

RCD Safety Switch

Battery Switch

LED Panel Lights

Overload Alarm

Output Indicator

Low Oil Alarm

ECO Throttle Switch

Data Center

240-Volt AC 15-Amp Outlet

LED Panel Lights

Frame Terminal

Panel Lights Switch

Reset Button

Battery Charging Inlet

Output Voltage (Volts): 120.0

Output Frequency (Hz): 50.0

Cumulative Run Time (hours): 00:00

Current Run Time (hh:mm): 01:58

Powering People Since 1886.

iGen4750PRO

Inverter Generator

Specifications

ENGINE		240 VOLT AC ELECTRICAL	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled	Voltage (V)	240
Displacement (cc)	190	Frequency (Hz)	50
Maximum Speed (rpm)	4,500	Number of Phases	1
Oil Capacity (mL)	600	Continuous Running Power (W) *	3,800
Oil Viscosity	SAE 10W-30	Maximum Starting Power (W)	4,750
Low Oil Shutdown	Yes	Continuous Running Current (A)	15.8
Low Oil Alarm Indicator	Yes	Voltage & Waveform Control	Digital Inverter, Pure Sine Wave Output
Spark Plug	Torch F7RTC	Total Harmonic Distortion (THD)	< 2.5%
Fuel	Unleaded Petrol # (91, 95 or 98 RON)	Receptacles	1 x 15 A, IP66
Fuel Tank Capacity (L)	12	Overload Protection	Electronic
Fuel Shutoff Valve	Yes, Independent	Overload Indicator	Yes
Starting Method	Local / Remote Electric and Recoil	Overload Reset	Push Button
Battery	12 V, Maintenance Free	RCD Safety Switch	Yes
Run Time @ 1/4 / Full Load	14 / 4.2 hours	Alternator	Brushless, Permanent Magnet
Noise Level @ 1/4 / Full Load	57 / 67 dB(A) @ 7 m	Output Ready Indicator	Yes
DIMENSIONS & WEIGHTS		Data Center Display	Output Voltage & Frequency, Current & Cumulative Run Times
Generator L x W x H (mm)	660 x 374 x 574	Control Panel Lights	LED, Operable At All Times
Generator Weight - Dry / Wet (kg)	36 / 46	PRODUCT CODES	
Packed L x W x H (mm)	750 x 460 x 588	Product Code	WP iGen4750PRO
Packed Weight (kg)	42	GTIN Barcode	9347923003161

Ethanol blends such as E10 are not recommended.

* Rated output at 1.0 power factor.



Plug-In Battery Charger



Extendable Handle



Included Accessories



Westinghouse

westinghouseoutdoorpower.com.au



Call us: (07) 5500 6027

Email: info@powermastergenerators.com.au

Specifications are subject to change without notice. 2026-03-25